

Drench Hose Eye Washer

Technical Data Sheet

Drench Hose Eye Washer

Model:SS-I250

SS-I250 Drench Hose Eye Washer unit meets the provisions of ANSI Z358.1-2014 as a primary eye wash. Spray assembly can be left as a fixed eye wash or it can be removed to use as a drench hose. Eliminates the need for separate eye washes and drench hoses. Spray head assembly has two spray outlet heads with dust covers mounted on stainless steel supply arms. Activated by stay-open, stainless steel valve. 1.5m reinforced PVC hose. Fully factory assembled and water tested. Complete with ANSI compliant identification sign.



Technical Details:

1.Space efficient design,specially suitable for laboratory used

2.Material:304 Stainless Steel

3.Valve:1/2" Stainless Steel stay-open valve

4.Spray Head:ABS plastic in yellow color

5.Handle:Making by rubber with unlock button

6.Wall Mounted Bracket:304 Stainless Steel with Nylon Clips

7.Hose:1.5 meter reinforce PVC hose

8.Flow valve build in to avoid secondary hurt

9.Water working pressure:0.2MPA-0.8MPA

10.Flow control:11.5L/Min

11.Standard:EN 15154-1&2,AS 4775:2007,ANSI Z358.1-2014

12.Gross Weight:1.3KGS,**Net Weight:**0.9KGS

13.Dimension:35.5cm*15cm*9cm,

Master carton:49cm*33cm*42cm,10set per carton