



KARBOR 3,5-SE

- Robust: High-strength synthetic casing, offering a long service life.
- Safe: for maximum loads of 140kg reducing the impact force to below 6kN.
- Swivel lower carabiner 976: to avoid entanglement and improve equipment performance.
- Fall indicator: in the event of a fall, the green line turns red, indicating the user's fall.
- Valid for horizontal use in factor 2 with risk of sharp edges of 0.5mm diameter - VG11.060:2014. For this purpose, it incorporates an energy absorber with protector.

Material	
Tape	Polyester 25mm
Carter	Synthetic

Standard	EN 360 VG 11.060:2014
Length (m)	3,5
Weight (Kg)	1,77
Stopping distance (m)	1,40
Height (mm)	425
Lenght (mm)	81
width (mm)	115
Load (Kg)	140
Static resistance	15 kN
Impact force	< 6 kN
Useful life(years)	10 of use + 2 of storage since date of manufacture

KARBOR CONNECTORS

Bottom connector 976	
Opening	20mm
Material	Steel
Resistance	23 kN
Lock	Automatic
Rotary	Yes
Fall Indicator	Yes

Top connector 981	
Opening	18mm
Material	Steel
Resistance	25 kN
Lock	Thread
Rotary	No
Fall Indicator	No