

Test Report

PPE against fall from a height EN 358:2018 Belts and Lanyards for work positioning or restraint

Report no: 2.21.07.07

Client: GRIZZLY TOOLS

Manufacturer: GRIZZLY TOOLS

Client order: T/0901

Order received: 2 June 2021

Model: JE3210SET-E

Dates of tests: 7 June 2021 to 13 July 2021

Signed:



Steven Sum, Laboratory Manager

Issued: 15 July 2021

Page 1 of 14

Conditions

This report may be reproduced and distributed to your clients, provided that it is reproduced and distributed in full.

Specimens will be disposed of four weeks from the date of this report, unless otherwise instructed.

Opinions, comments and interpretations expressed in this report are shown in italics.

Copies of INSPEC interpretations referenced in this report are available upon request.

Tests marked ☒ are not included in our ANAB Scope of Accreditation.

This report has been provided in accordance with our standard Terms of Business, which can be viewed at, and printed from:

<http://inspec-international.com/ToB.pdf>

If you have difficulty accessing the Terms of Business, you may contact us for a copy.

Summary of assessment*

Clause	Requirement	Assessment (See Key)
4.1	Design, construction and ergonomics	Pass
4.2	Materials	Ltd
4.3	Connectors	
4.4	Static strength	Pass
4.5	Dynamic strength	Pass
4.6	Corrosion resistance	Pass
4.7 / 6	Marking	Pass
4.7 / 7	Information supplied by the manufacturer	Pass

Key

	Shading shows the clauses requested. Any other clauses were not requested.
Pass	Requirement satisfied.
Ltd	Testing requested was insufficient completely to verify compliance with the clause. Refer to the "Result details" section for more information.
Fail	Requirement not satisfied. Refer to the "Result details" section for more information.
NAs	Assessment not carried out.
NAp	Requirement not applicable.
NT	Requested but not tested due to early termination following failure.

* Assessment relates only to those specimens which were tested and are the subject of this report.

Submission details

Product	Quantity	Date received	INSPEC specimen no. (2J125 +)
Working positioning lanyard, model JE3210SET-E	04	3 June 2021	01 to 04

Procedures

The specimens detailed within the submission above were used for the tests covered by this report.

Testing was performed in accordance with EN 358:2018 unless otherwise specified below. Reference should be made to the standard when reading this report.

Unless stated otherwise, specimens were tested in the condition as received by INSPEC.

Testing was performed at INSPEC's laboratory in Kunshan, China.

Result details**4.1 Design, construction and ergonomics****4.1.3 Work positioning and restraint lanyard**

Specimen 2J12501 was assessed.

- | | | |
|---------|--|------|
| 4.1.3.1 | The work positioning lanyard was adjustable. | Pass |
| | Involuntary release of the work positioning lanyard was not possible. | Pass |
| 4.1.3.2 | It was possible to connect the work positioning lanyard to a waist belt at one end and to an anchor point at the other end directly or by a connector. | Pass |
| 4.1.3.3 | This clause is not applicable to the type of lanyard tested. | NAP |
| 4.1.3.4 | This clause is not applicable to the type of lanyard tested. | NAP |
| 4.1.3.5 | This clause is not applicable to the type of lanyard tested. | NAP |

4.1.4 Length adjustment device

Specimen 2J12502 was assessed.

- | | | |
|---------|---|------|
| 4.1.4.1 | The specimen was free from sharp edges and burrs. | Pass |
| 4.1.4.2 | The length adjustment device was non-detachable. | Pass |
| 4.1.4.3 | It was possible to adjust the length of the work positioning lanyard while in use as described in the information supplied by the manufacturer. | Pass |
| 4.1.4.4 | The slippage of the lanyard through the length adjustment device was 3 mm. This did not exceed the 50 mm specified. | Pass |

4.2 Materials

Specimen 2J12501 was assessed.

- | | | |
|-------|--|------|
| 4.2.1 | Possible effects of contact by materials of the waist belts and lanyards with the skin of the user were not assessed. Manufacturer to certify. | NAs |
| 4.2.2 | The materials used for fibre rope, webbing and threads and their characteristics were not assessed. Manufacturer to certify. | NAs |
| 4.2.3 | Threads used for sewing the specimen were black colour. This contrasted with the white colour of the rope. | Pass |
| 4.2.4 | This clause is not applicable to the type of lanyard tested. | NAP |

4.4 Static strength

Specimen 2J12502 was assessed.

- | | | |
|-------|--|------|
| 4.4.1 | Not applicable. | NAP |
| 4.4.2 | Not applicable. | NAP |
| 4.4.3 | Not applicable. | NAP |
| 4.4.4 | The lanyard with a length adjustment device withstood the 15 kN force applied for 3 minutes. | Pass |

4.5 Dynamic strength

Specimen 2J12503 was assessed

- | | | |
|-------|--|------|
| 4.5.1 | This clause is not applicable to the type of product tested. | NAP |
| 4.5.2 | This clause is not applicable to the type of product tested. | NAP |
| 4.5.3 | Following the drop test, the rigid test mass was held clear of the ground. | Pass |

4.6 Corrosion resistance

Specimen 2J12504 was assessed.

When tested in accordance with 5.8, all metallic elements incorporated into the specimen did not show evidence of corrosion of the base metal.	Pass
--	------

6 Marking

Marking labels were assessed against the requirements of clause 4.8 of EN 365:2004 and the results are given on page 12 of this report.

The same specimen was assessed against the requirements of EN 358 and the results are detailed below.

Markings labels were provided electronically and used for assessment.

On the lanyard,

- | | | |
|----|---|------|
| a) | The specimen was marked with the maximum rated load in kilograms, thus "100 kg" | Pass |
| b) | The specimen was marked with the maximum lanyard length, thus "2000 mm" | Pass |

6.1 Information supplied by the manufacturer

The information was assessed against the requirements of clauses 4.1 to 4.7 of EN 365:2004 and the results are given on page 8 to 11 of this report, and shall in addition contain the following information and advice.

The language assessed was English.

- | | |
|---|------|
| a) For the waist belt, the size range in cm, the correct way to put it on and instructions on how to obtain the optimum fit; | NAP |
| b) For the waist belt, the essential need to regularly check fastening and adjustment elements during use; | NAP |
| c) That the waist belt is approved for a user, including tools and equipment, with a weight of up to 150 kg; | NAP |
| d) For the waist belt identification of attachment elements, the correct method of connecting to them, and a clear and unambiguous statement which states the purpose of each attachment element; | NAP |
| e) A warning that the equipment is not suitable for fall arrest purposes and that a waist belt should not be used if there is a foreseeable risk of the user becoming suspended or being exposed to unintended tension by the waist belt; | Pass |
| f) That when using the work positioning system, the user normally relies on the equipment for support, therefore it is essential to consider the need of using a back-up, e.g. a fall arrest system; | Pass |
| g) An instruction to how to position and/or adjust the work positioning lanyard so that the lanyard is kept taut; | Pass |
| h) For work positioning a warning to emphasize that it is essential for safety to use an anchor point positioned at or above waist level. | Pass |

EN 365:2004, Clause 4.1 to 4.7, Instructions**4.1 General**

The manufacturer shall prepare instructions for use, for maintenance and for periodic examination for each item of PPE or other equipment, in the official languages of the country of destination.

The language assessed was English.

Note. The instruction for use, for maintenance and for periodic examination may be supplied in separate documents.

4.2 Instructions for use

4.2.1 The instructions for use shall be in a written format, shall be clear, legible and unambiguous, and shall contain appropriate detail, supplemented by diagrams if necessary, to enable the PPE or other equipment to be used correctly and safely. Pass

4.2.2 The instructions for use shall include:

- | | | |
|----|--|------|
| a) | Name and contact details of the manufacturer or authorised representative as appropriate; | Pass |
| b) | Statements describing the equipment, its intended purpose, application and limitations; | Pass |
| c) | Warning about medical conditions that could affect the safety of the equipment user in normal and emergency use; | Pass |
| d) | Warning that the equipment shall only be used by a person trained and competent in its safe use; | Pass |
| e) | Warning that a rescue plan shall be in place to deal with any emergencies that could arise during the work; | Pass |
| f) | Warning against making any alterations or additions to the equipment without the manufacturer's prior written consent, and that any repair shall only be carried out in accordance with manufacturer's procedures; | Pass |
| g) | Warning that the equipment shall not be used outside its limitations, or for any purpose other than that for which it is intended; | Pass |
| h) | Advice as to whether the equipment should be a personal issue item, where this is applicable; | Pass |
| i) | Sufficient information to ensure the compatibility of items of equipment when assembled into a system; | Pass |
| j) | Warning of any dangers that may arise by the use of combinations of items of equipment in which the safe function of any one item is affected by or interferes with the safe function of another; | Pass |
| k) | Instruction for the user to carry out a pre-use check of the equipment, to ensure that it is in a serviceable condition and operates correctly before it is used; | Pass |

Note1. A pre-use check by the user may not be applicable in the case of certain parts of equipment for emergency use which have been pre-packed or sealed by a competent person.

- | | | |
|----|---|------|
| l) | Features of the equipment that require the pre-use check, the method of checking, and the criteria against which the user can decide whether or not the equipment is defective; | Pass |
|----|---|------|

- | | |
|--|------|
| m) Warning stating that it is essential for safety that equipment is withdrawn from use immediately should: | |
| 1) any doubt arise about its conditions for safe use or; | Pass |
| 2) it have been used to arrest to fall | Pass |
| and not used again until confirmed in writing by a competent person that it is acceptable to do so; | |
| n) Requirements of the anchor device or structural member chosen to serve as the anchor point(s), in particular the minimum required strength, the suitability and the position; | Pass |
| o) Where relevant, instruction on how to connect to the anchor device or structure; | Pass |
| p) Where relevant, an instruction detailing the correct harness attachment point to use, and how to connect to it; | N/Ap |
| q) For equipment intended for use in fall arrest systems, a warning to emphasise that it is essential for safety that the anchor device or anchor point should always be positioned, and the work carried out in such a way, as to minimise both the potential for falls and potential fall distance. Where is it essential that the anchor device/point is placed above the position of the user, the manufacturer shall make a statement to that effect; | Pass |
| r) Where relevant, an instruction that a full body harness is the only acceptable body holding device that can be used in a fall arrest system; | Pass |
| s) For equipment intended for use in fall arrest systems, a warning to emphasise that it is essential for safety to verify the free space required beneath the user at the workplace before each occasion of use, so that, in the case of a fall , there will be no collision with the ground or other obstacle in the fall path; | Pass |
| t) Information on the hazards that may affect the performance of the equipment and corresponding safety precautions that have to be observed, e.g. extremes of temperature, trailing or looping of lanyards or lifelines over sharp edges, chemical reagents, electrical conductivity, cutting, abrasion, climatic exposure, pendulum falls; | Pass |
| u) Instruction as relevant on how to protect the equipment against damage during transportation; | Pass |
| v) Information on the meaning of any markings and/or symbols on the equipment; | Pass |
| w) Statement describing the equipment model, type, identification marks and, if appropriate, the document and year to which it conforms; | Pass |
| x) Where it is a requirement that an EC type examination be carried out by a Notified Body, the name, address and identification number of the Notified Body involved with the design stage and of the Notified Body involved in the production control phase; | Pass |
| y) Statement of any known limit to the safe useable life of the product or any part of the product and/or advice on how to determine when the product is no longer safe to use; | Pass |
| z) Warning that it is essential for the safety of the user that, if the product is re-sold outside the original country of destination, the reseller shall provide instructions for use, for maintenance, for periodic examination and for repair in the language of the country in which the product is to be used. | Pass |

Note 2. Any additional relevant information specific to the item of equipment should also be provided.

4.3 Instructions for maintenance

- | | | |
|-------|--|------|
| 4.3.1 | The maintenance instruction shall be clear, legible and unambiguous, and shall contain appropriate detail, supplemented by diagrams if necessary, to enable the PPE or other equipment to be maintained correctly and safely. | Pass |
| 4.3.2 | The maintenance instructions shall include: | Pass |
| a) | Cleaning procedures, including disinfection where applicable, without causing adverse effect on the materials used in the manufacture of the equipment, or to the user, and a warning that the procedure is to be strictly adhered to; | Pass |
| b) | Where appropriate, a warning that, when the equipment becomes wet, either from being in use or when due to cleaning, it shall be allowed to dry naturally, and shall be kept away from direct heat; | Pass |
| c) | Storage procedures, including all necessary preventative requirements where environmental or other factors could affect the condition of components, e.g. damp environment, sharp edges, vibration, ultraviolet degradation; | Pass |
| d) | Other maintenance procedures as relevant to the equipment, e.g. lubrication. | Pass |

4.4 Instructions for periodic examination

Instructions for periodic examination shall include:

- | | | |
|----|--|------|
| a) | Warning to emphasize the need for regular periodic examinations, and that the safety of users depends upon the continued efficiency and durability of the equipment; | Pass |
| b) | Recommendation in regard to the frequency of periodic examinations, taking account of such factors as legislation, equipment type, frequency of use, and environmental conditions. The recommendation shall include a statement to the effect that the periodic examination frequency shall be at least every 12 months; | Pass |
| c) | Warning to emphasize that periodic examinations are only to be conducted by a competent person for periodic examination and strictly in accordance with the manufacturer's periodic examination procedures; | Pass |
| d) | Where deemed necessary by the manufacturer, e.g. due to the complexity or innovation of the equipment, or where safety critical knowledge is needed in the dismantling, reassembly, or assessment of the equipment, (e.g. a retractable type fall arrester), an instruction specifying that periodic examinations shall only be conducted by the manufacturer or by a person or organisation authorised by the manufacturer; | Pass |
| e) | Requirement to check the legibility of the product markings. | Pass |

4.5 Instructions for repair

Where the manufacturer permits repair, repair instructions shall be supplied in the official languages of the country in which the item is in service. These instructions shall include a statement to the effect that any repair shall only be conducted by a competent person for repair, who has been authorised by the manufacturer, and that the repair procedure shall be strictly in accordance with the manufacturer's instructions.	NAp
--	-----

Repair was not allowed by the manufacturer

4.6 Records

Advice shall be given that a record is kept for each component, subsystem and system. The record should contain headings for, and spaces to allow entry of, the following details:

- | | |
|--|------|
| a) Product, (e.g. full body harness), model and type/identification and its trade name; | Pass |
| b) Name and contact details of the manufacturer or supplier; | Pass |
| c) Means of identification, which could be the batch or serial number; | Pass |
| d) Where applicable, the year of manufacturer or life expiry date, (refer to 4.2.2 y); | Pass |
| e) Date of purchase; | Pass |
| f) Any other information as necessary, e.g. maintenance and frequency of use; | Pass |
| g) Date first put into use; | Pass |
| h) History of periodic examinations and repairs, to include: | |
| 1) dates and details of each periodic examination and repair, and the name and signature of the competent person who carried out the periodic examination or repair; | Pass |
| 2) next due date of periodic examination. | Pass |

Note. It is the responsibility of the user organisation to provide the record and enter into the record the details required.

4.7 Periodic examination

Manufacturers shall provide all the necessary information and equipment e.g. instructions, checklists, spare parts lists and special tools etc, to enable periodic examinations to be carried out by a competent person.	Pass
--	------

EN 365:2004, Clause 4.8, Marking

- 4.8.1** Each item of PPE or other equipment shall be clearly, indelibly and permanently marked by the manufacturer in the official language of the country of destination, by any suitable method not having a harmful effect on the materials so marked, and shall include at least:

The language assessed was English.

- a) means of identification, e.g. manufacturer's name, supplier's name, or trademark; Pass

Note 1. When PPE is marked with the supplier's name this should be with the approval of the Notified Body.

- b) manufacturer's production batch or serial number or other means of traceability; Pass

- c) model and type/identification; Pass

- d) number and year of the document to which the equipment conforms; Pass

- e) pictogram or other method to indicate the necessity for users to read the instructions for use; Pass

Note 2: Any additional relevant marking specific to the item of equipment should also be included.

- 4.8.2** The characters in the markings shall be legible and unambiguous. Pass

Estimates of the uncertainty of measurement

Clause	Test		Uncertainty
4.1	Design, construction and ergonomics		±0.6 mm
4.2	Material		Not applicable
4.3	Connectors		See report
4.4	Static strength	Tensile test	See Note 1
		Slippage	±0.7%
4.5	Dynamic strength		See Note 1
4.6	Corrosion resistance		See Note 1
4.7 / 6	Marking		Not applicable
4.7 / 7	Information		Not applicable

Note 1 The acceptance criterion for this test is a straightforward "Pass/Fail", rather than a numerical value. Consequently, as there is no value to be reported, uncertainty has not been reported either.

Note 2 The uncertainty value is based on a standard uncertainty multiplied by a coverage factor $k = 2$, which provides for a confidence level of approximately 95%. Values expressed as a percentage (%) are relative.

Note 3 It should be noted that the above values have not been taken into account when making assessment to the pass/fail criteria.

ANNEX

This Annex comprises one section.

1. Photograph of the product tested. (1 page)

END OF REPORT

**Jinhua Jech Tools Co., Ltd. –
Working positioning lanyard, model JE3210SET-E**

